

超塑烯® UE632

EVATHENE® UE632

乙烯醋酸乙烯酯共聚合樹脂



ETHYLENE-VINYL ACETATE COPOLYMER RESINS

概述	Description
超塑烯® UE632 是一種乙烯醋酸乙烯酯共聚合樹脂，可運用在注塑發泡、異型擠壓以及吹膜擠壓設備。	EVATHENE® UE632 is an ethylene-vinyl acetate copolymer resin (EVA) for use in foam injection, profile extrusion, and blown film extrusion machine.
特性	Characteristics
<ul style="list-style-type: none"> ◇ 柔軟 ◇ 彈性 ◇ 抗外界應力龜裂性很強 ◇ 低溫柔軟性很好 	<ul style="list-style-type: none"> ◇ Flexibility ◇ Elasticity ◇ Great resistance to environmental stress cracking ◇ Low temperature flexibility
應用	Applications
<ol style="list-style-type: none"> 1. 鞋材發泡 2. 替代軟質 PVC、橡膠與其他彈性材料 	<ol style="list-style-type: none"> 1. Shoe sole foaming 2. Replace the flexible PVC, rubbers and other elastomers

物理性質 Physical Properties

項目 Properties	試驗方法 Test Method	數 值 Typical Value
VA 含量 VA Content (%)	USI	22
熔融指數 Melt Index (g/10min)	ASTM D1238	2.2
密度 Density (g/cm ³)	ASTM D792	0.942
斷裂點抗張強度(模片) Tensile Strength(Molded) (Break) (kg/cm ²)	ASTM D638	170
斷裂點伸長率 (模片) Ultimate Elongation(Molded) (%)	ASTM D638	820
低溫脆裂溫度 Low Temperature Brittleness(°C/F50)	ASTM D746	<-76
衛氏軟化溫度 Vicat Softening Temperature (°C)	ASTM D1525	58
熔點 Melt Point (°C)	ASTM D3418	82
硬度(蕭氏 A) Hardness (Shore A)	ASTM D2240	86

據本公司所知，上述資料應屬正確無誤，惟因使用時之情況非受本公司管制，所以本公司對上述所作之一切建議，恕不負保證之責。
The information contained herein is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all risks of such use are assumed by users.