

# 聯塑烯® LH5590 UNITHENE® LH5590 高密度聚乙烯樹脂 HIGH DENSITY POLYETHYLENE RESINS



## 概述

聯塑烯® LH5590 是一種高流動性的射出級高密度聚乙烯樹脂，具有良好的加工性和熱穩定性，可運用於薄壁射出成型、粉末塗膠、色母造粒。

## Description

UNITHENE® LH5590 is a high-flow injection grade high density polyethylene resin (HDPE) that exhibits enhanced processing and thermal stability for use in thin wall injection molding, powder coating, and master batch.

## 特性

◇ 極佳的加工性

## Characteristics

◇ Excellent processability

## 應用

1. 薄壁容器
2. 粉末塗膠
3. 色母造粒

## Applications

1. Thin wall injection molding container
2. Powder coating
3. Master batch

## 物理性質 Physical Properties

項目 Properties	試驗方法 Test Method	數 值 Typical Value
熔融指數 Melt Index (g/10min)	ASTM D1238	90
密度 Density (g/cm <sup>3</sup> )	ASTM D792	0.955
降伏點抗張強度 Tensile Strength (Yield) (kg/cm <sup>2</sup> )	ASTM D638	250
斷裂點伸長率 Ultimate Elongation (%)	ASTM D638	20
抗衝擊強度 Izod Impact Strength(kg-cm/cm)	ASTM D256	2.7
衛氏軟化溫度 Vicat Softening Point(°C)	ASTM D1525	120
熔點 Melt Point (°C)	ASTM D3418	128
硬度(蕭氏 D)Hardness (Shore D)	ASTM D2240	68

據本公司所知，上述資料應屬正確無誤，惟因使用時之情況非受本公司管制，所以本公司對上述所作之一切建議，恕不負保證之責。The information contained herein is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all risks of such use are assumed by users.