

FL-202WA

織物用水性阻燃劑

FL-202WA 是一種高效的環保阻燃水性阻燃劑，具有顯著的阻燃性能，與水性聚氨酯(PU)具有優異的相容性。FL-202WA 特別適用於合成織物上的阻燃塗層，包括聚酯布，聚酯/天然纖維混紡布。

產品特徵:

- 液態水溶性，與水性聚氨酯(PU)具有優異的相容性，易於使用
- 特殊複合配方，阻燃效果佳
- 易於保存，不易沉降
- 光及熱穩定性好，不易黃化，不影響底布顏色
- 極低的揮發性
- 無鹵素，符合 ROHS、REACH 等國際環保法規
- 適用於國際織物耐燃法規，包含 JIS L1091、NFPA 701、M1 等

產品資訊:

項目	單位	數值
外觀	--	白色乳液
黏度(25°C)	cps	8000~12000
比重	g/cm ³	1.35~1.45
ph 值	--	5~7
固含量	%	62±2

包裝:

- 20kg 桶裝.

Values included in this data sheet are based on limited laboratory test specimens. These values are typical values and are not meant to be used for setting maximum or minimum values for specification purposes. Any determination of the suitability of the materials shown in this property data sheet for use by the end user is the sole responsibility of the user, who must assure themselves that the material as subsequently processed meets the need of his particular product or use. To the best of our knowledge the information in this publication is accurate and reliable, USI does not assume any liability whatsoever for the accuracy of this information.

USI Corporation

No.37, Ji-Hu Rd., Nei-Hu Dist., Taipei City 11492, Taiwan

(886-2)-8751-6888 www.usig.com