

FL-302WR

織物用水性阻燃塗佈膠

FL-302WR 是一種高效的環保阻燃水性阻燃塗佈膠，不含重金屬與鹵素，布面上膠後具有顯著的阻燃性能。FL-302WR 特別適用於合成織物上的阻燃塗層，包括聚酯布，聚酯/天然纖維混紡布。

產品特徵：

- 液態水溶性，可直接塗佈(刀塗、凹版上膠)或加水稀釋後塗佈使用，應用範圍廣
- 特殊複合配方，阻燃效果佳
- 易於保存，不易沉降
- 極低的揮發性
- 無鹵素，符合 ROHS、REACH 等國際環保法規
- 適用於國際織物耐燃法規 BS-5852

產品資訊：

項目	單位	數值
外觀	--	白色乳液
黏度(25°C)	cps	20,000~40,000
比重	g/cm ³	1.15~1.25
ph 值	--	5.5~6.5
固含量	%	58~62

包裝：

- 20kg 桶裝。

Values included in this data sheet are based on limited laboratory test specimens. These values are typical values and are not meant to be used for setting maximum or minimum values for specification purposes. Any determination of the suitability of the materials shown in this property data sheet for use by the end user is the sole responsibility of the user, who must assure themselves that the material as subsequently processed meets the need of his particular product or use. To the best of our knowledge the information in this publication is accurate and reliable, USI does not assume any liability whatsoever for the accuracy of this information.

USI Corporation

No.37, Ji-Hu Rd., Nei-Hu Dist., Taipei City 11492, Taiwan

(886-2)-8751-6888 www.usig.com